

**Series 4, island cooker hood, 90 cm,
Stainless steel
DIB97IM50**

B



Optional accessories

DHZ1231 Adapter for roof inclination left/right, DHZ1241 Adapter for roof inclination front/back, DHZ1246 Chimney extension 1100 mm, DHZ1251 Extension for mounting kit 500 mm, DHZ1253 Extension for mounting kit 1000 mm, DHZ1256 Chimney extension 1600 mm, DHZ5346 Standard odor filter (replacement), DHZ5385 Standard recirculation kit, DIZ2CB1I4 Clean Air Standard recirculation kit, DIZ2CX5C6 Clean Air Plus recirc. kit external, DIZ2FX5D1 Long Life recirculation kit external, DZZ0XX0P0 Long Life odor filter (replacement), DZZ1XX1B6 Clean Air Plus odor filter (replacement), DZZ2CB1B4 Clean Air Standard odor filter (repl.)

The island chimney hood: the perfect solution for your cooking island thanks to flexible ceiling mounting.

- **Especially Silent:** maximum hood performance, minimum noise.
- **Easy-to-Clean Interior:** hidden screws and cables along with rounded edges make cleaning easy.
- **Grease filtration level:** filters out over 85% of the grease from kitchen air
- **TouchSelect control:** Quickly select hood settings via touch.
- **LED Illumination:** The energy-saving lighting provides white and good lighting for the hob area.

Technical Data

Typology : Island/Ceiling
 Length electrical supply cord : 130 cm
 Height of the chimney : 691-871/691-991 mm
 Height of product, without chimney : 53 mm
 Minimum distance above an electric hob : 550 mm
 Minimum distance above a gas hob : 650 mm
 Net weight : 29.2 kg
 Type of control : Electronic
 Maximum output air extraction : 438 m³/h
 Boost position output recirculating : 527 m³/h
 Maximum output recirculating air : 390 m³/h
 Boost position air extraction : 754 m³/h
 Number of lights : 4
 Noise level : 57 dB(A) re 1 pW
 Diameter of air outlet : 150 / 120 mm
 Grease filter material : Washable aluminium
 EAN code : 4242005086269
 Connection Rating : 256 W
 Fuse protection : 10 A
 Voltage : 220-240 V
 Frequency : 60; 50 Hz
 Plug type : Gardy plug w/ earthing
 Installation typology : Island



Series 4, island cooker hood, 90 cm, Stainless steel DIB97IM50

The island chimney hood: the perfect solution for your cooking island thanks to flexible ceiling mounting.

- Energy Efficiency Class: B (at a range of energy efficiency classes from A+++ to D)
- Average Energy Consumption: 74.3 kWh/year
- Blower Efficiency Class: B*
- Lighting Efficiency Class: A
- Grease Filtering Efficiency Class: B
- Noise min./max. Normal Level: 45/57 dB

Variant:

Design:

Technical information

Performance

Power:

Environment and safety:

Comfort:

Measures:

Technical information

- Island Hood Brushed steel
- 90 cm wide
- 90 cm Island chimney hood, Brushed steel
- Suitable for ducted or re-circulated extraction
- For recirculated extraction standard recirculation kit or Clean Air Plus recirculation kit (accessory) needed
- Ceiling mounted hood
- TouchControl
- Electronic controls
- TouchControl with Electronic display
- 3 speeds plus intensive setting via TouchControl
- Electronic controls via TouchControl with Electronic display
- TouchControl (3 speeds plus intensive setting) with Electronic display
- 3 speeds plus intensive setting
- Automatic revert setting, 6 minutes
- easy to clean Innerframe
- Energy efficient capacitor motor
- 4 x 1,5 W LED
- Light Intensity: 409 lux
- Colour Temperature: 3500 K
- Cassette with alu frame
- Metal grease filter, dishwasher safe
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 438 m³/h
Intensive 754 m³/h
- Extraction rate exhaust air according to EN 61591 max. 754 m³/h
- Extraction rate according to EN 61591 ø 15 cm:
max. Normal use 438 m³/h
Intensive 754 m³/h
- Extraction rate exhaust air according to EN 61591:
max. normal use 438 m³/h, intensive 754 m³/h
- Dimensions recirculating with CleanAir Plus recirculation kit (HxWxD): 812-1044 x 898 x 600 mm
- Additional noise insulation
- Noise level according to EN 60704-2-13 at max. normal use exhaust air: Noise, max. speed in normal use: 57 dB(A) re 1 pW
- Noise level according to EN 60704-2-13 exhaust air:
Max. normal use: 57 dB(A) re 1 pW
Intensive: 68 dB(A) re 1 pW
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- with one-way flap
- Max. extraction rate: 754 m³/h
- Dimensions exhaust air (HxWxD): 744-924 x 898 x 600 mm
- Dimensions recirculating (HxWxD): 744-1044 x 898 x 600 mm
- Power rating: 256 W
- Electrical cable length 1.3 m
- Voltage: 220 - 240 V
- With the Clean Air Plus recirculation kit (available as optional accessory) your appliances reaches:
Extraction rate in recirculation mode: Max. normal use: 390 m³/4 h
Intensive: 527 m³/h
Noise level in recirculation mode: Max. normal use: 67 dB(A) re

** In accordance with the EU-Regulation No 65/2014*

**Series 4, island cooker hood, 90 cm,
Stainless steel
DIB97IM50**

